



Technical Specifications

GP-2 190 4S | M.Y 2026

ENGINE TYPE	Daytona 190 cc horizontal single cylinder 4 stroke, Air Cooling
VALVE ACTUATION	Single camshaft, SOHC - 4 valves
FUEL	Unleaded Petrol (N.O. min 95)
BORE & STROKE	62mm x 62mm
DISPLACEMENT	187,18 cc
FUEL SYSTEM	Carburetor DELLORTO PHBH 28 BD Ohvale Settings, Racing air filter. Carburetion update
IGNITION	Electronic, external spark plug & coil (CDI with Rev Limiter)
STARTER	Kick starter with decompression system
EXHAUST SYSTEM	Exhaust pipe in stainless steel. Under saddle single silencer Arrow in titanium. Ready for DB Killer
LUBRICATION	Wet sump lubrication system, with oil radiator. Oil quantity: 1 Liter
TRANSMISSION	4 Speed, N - 1 - 2 - 3 - 4 Ohvale setting
PRIMARY DRIVE	Gears
SECONDARY DRIVE	Regina chain gold series. Ergal Sprocket. Drive ratio 17/36 (2,117)
CLUTCH	STANDARD: 6 Plate wet clutch RACE: Dedicated slipper clutch system
FRAME	High-strength steel trellis frame, robotic welding, new swingarm pivot position
FRONT SUSPENSION	STANDARD: Ø 33mm upside-down fork & CNC foot fork. Spring config. K7-K7 and adjustable spring preload. Increased fork stroke PRO/RACE: Ø 35mm fully adjustable Ohvale racing fork. Spring config. K7-K8. Increased fork stroke
REAR SUSPENSION	Aluminium swing-arm. Monoshock with piggy-back. Fully adjustable: hydraulic compression and rebound damping, spring preload & wheelbase. Spring config. K140
FOOTREST	STANDARD: CNC-machined components, reinforced and black anodization RACE: CNC-machined parts + Electronic quickshifter
FRONT BRAKING SYSTEM	STANDARD: Single floating disc Ø 220mm, 4.5mm tk. Brembo radial caliper (4 pistons D24). Sintered brake pads. Brembo axial master cylinder PS 10/19 with integrated tank & braided steel hose PRO/RACE: Standard config. + Floating disc Ø 230mm, 4.5mm tk
REAR BRAKING SYSTEM	Single disc Ø 180mm. J. Juan floating caliper (single piston D25). Axial master cylinder with integrated tank & braided steel hose
RIMS	Aluminum alloy wheels, design by Ohvale. Front 2,50 × 12" - Rear 3,00 × 12"
TYRES	Tubeless Pirelli slick. Front 100/90 - 12", Rear 120/80 - 12"
FAIRINGS	Fiberglass racing fairings RACE: new OHVALE racing seat
DIMENSIONS (DEFAULT SETTINGS)	Max. lenght: 1610mm / Max. width: 740mm (at the handlebar) Max. height: 915mm / Saddle height 725mm
DRY WEIGHT	71 Kg (without any liquid)
FUEL TANK CAPACITY	3,5 Liters

■ New features Model Year 2026